TG D35

Dynamic Microphone

Order # 708.429





FEATURES

- Supercardioid polar pattern
- Rugged plastic housing with metal grille
- Perfect for toms and snare
- Flexible use with all instruments with a high sound pressure level
- Including MKV 87 microphone clamp

APPLICATIONS

Due to the tuned frequency response, the TG D35 is ideal for miking toms and snare drums. Its powerful sound is not only great for drums; the TG D35 is suitable for the use with all instruments with a high sound pressure level such as percussion instruments like congas or bongos.

The compact design and the lightweight, rugged plastic housing allow easy positioning. Due to the supercardioid polar pattern a high channel separation can be achieved, while the boost of low-frequency signal sources ensures a powerful sound. Due to the dynamic capsule even high volumes are transmitted without distortion.

The patented MKV 87 microphone clamp is included.

TECHNICAL SPECIFICATIONS

Transducer type	Dynamic
Operating principle	Pressure gradient
Polar pattern	Supercardioid
Frequency response:	
Close miking	50 - 14,000 Hz

Distant miking (distance 1 m) 60 - 14,000 Hz
Open circuit voltage 2.2 mV/Pa (-53 dBV) ±3 dB

Nominal impedance 600 Ω

Load impedance. $\geq 2 \text{ k}\Omega$

Connector XLR, 3-pin, male

Dimensions:

Length ... 72 mm
Shaft diameter ... 28.5 mm
Head diameter ... 35 mm
Weight (without clamp) ... 95 g

COMPONENTS

TG D35 Dynamic drum microphone (supercardioid) Order # 649.724 MKV 87 Microphone clamp Order # 459.356

OPTIONAL ACCESSORIES

BMC 05 FM Standard microphone cable XLR-XLR, length 5 m Order # 434.787

BMC 10 FM Standard microphone cable XLR-XLR, length 10 m . . . Order # 434.795

1 of 2

beyerdynamic GmbH & Co. KG Theresienstr. 8 | 74072 Heilbronn – Germany Tel. +49 (0) 71 31 / 617 - 0 | Fax +49 (0) 71 31 / 617 - 204 info@beyerdynamic.de | www.beyerdynamic.com



TG D35

FREQUENCY RESPONSE & POLAR PATTERN

This frequency response curve (measuring tolerance ±3 dB) and polar pattern correspond to a typical production sample for this microphone.



